

DataPage II LITE



The Scope™ DataPage II Lite is a compact desktop numeric encoder/transmitter on-site paging terminal. The unit has a 9,999 pager capacity. The system operates on 12 Volts DC supplied by a 115VAC-wall adapter. The unit comes with a four-inch helical antenna, BNC terminated.



FEATURES

- ◆ Accommodates 9,999 numeric pages
- ◆ Range up to 1 mile
- ◆ Ease of Operation
- ◆ Select 512 or 1200 Baud Transmission
- ◆ Industry Standard POCSAG Transmission



Data Page II

LITE

SPECIFICATION SHEET

Operating / Input Voltage	12 Volts DC, Wall AC Adapter UL Approved
Operating Current	100mA standby, 300mA Transmit
Frequency	457.575 Mhz
Adjacent Channel	<200nW @4.5Khz deviation at 25Khz channel spacing @ 512 or 1200 Baud
Deviation	± 4.5 Khz
Stability	± 2.5ppm @ 14° to 132°F
Paging Format	POCSAG
RF Baud Rate	512, 1200
Type Accepted	FCC Part 90
FCC ID	JRNUSASERILINK
Size	7.75"W x 1.75"H x 7.5"D
Weight	1.6 Lbs without AC Adapter
Antenna	Electrical ¼ Wave, 4" Helical 90° BNC Terminated