

**SLDW**

## Low Power UHF Transmitter

This Programmable UHF Transmitter has 4 dry contact inputs that can have its own configured message up to 21 characters along with a reset message. Unit can be configured with wired input or magnet input. The SLDW is programmable using the optional programming kit.

Can be installed as a Door or Window Alert transmitter using the magnet input feature



---

### Features

- Rugged, Ergonomically designed casing
- Water resistant
- 4 Trigger Zones
- Frequency Programmable  
430 Mhz – 460 Mhz
- Test Call Function
- Low Power “Sleep Mode”

### Specification

- Internal Battery – 9.0v
- Current - <50mA @10mW
- Frequency – 433 – 460 Mhz
- Channel Spacing 12.5Khz @ 2.5Khz deviation

### Technical

- Configurable message for each of the 4 triggers (up to 21 characters)
- Trigger – normally open, or normally closed or toggle
- Trigger 4 – can be used to reset all contacts when other contacts set to repeat till reset
- Test call repeats messages up to 18 hours
- Low power message (up to 21 chars)
- Shutdown message (up to 21 chars)
- Contact response time = 30mS min, 50mS max
- FCC -

**3900 Woodlake Blvd. – Suite 208 – Greenacres, Florida 33463**

**Tel: 561.969.6976 Fax: 561.969.7134**